

1/14




Fig. 1




Fig. 2




Fig. 3

2/14




Fig. 4






Fig. 5



5/14




Fig. 9




Fig. 10  
(Prior Art)

6/14




Fig. 11

7/14




Fig. 12







Fig. 13

8/14



9/14




Fig. 17




Fig. 18






Figure 19




Figure 20




Figure 21




Figure 22

Method:	Example 1	Example 2	Example 3	Example 4	Example 5
V-Bend – Product no Keel	Peak Slope	43 5.0	23 2.9	23 3.0	20 2.6
V-Bend – Product with Keel	Peak Slope	32 1.2	14 0.5	11 0.5	9 0.4
L-Bend – Product with Keel	Peak Slope	211 3	42 1.2	83 2.5	55 1.6
Keel Stiffness	Peak Slope	< 10* < 0.1 *	21 1.6	38 10	30 5
Soiling ....up to 2.0g loads	%	70	27	17	n/a
HGW Capacity @ 70g/sqcm					
In Blood	grams	7.3	7.3	7.3	7.3
In Urine	grams	11.0	11.0	11.0	11.0

\* value below measurement capability, use only as a guide

12/14




Figure 24




Figure 25




Figure 26




Figure 27




Figure 28




Figure 29

17/14



Figure 30




Figure 31

308

308

### IL3 Core Technology

Fibrous AGM and needle punching dramatically increase core capacity




Figure 32